

www.purepro.net

DOUBLE O'RING FILTER HOUSING

PUREPRO DOUBLE O'RING FILTER HOUSINGS

- Accepts 2.5" Nominal 10" Length Cartridges
- Opaque Housings are NSF Listed
- 1/4", 3/8" and 1/2" Female NPT Ports Standard
- Optional 3/8" Quick Connect Ports are Available



Tested and Certified by International under ANSI Standard 42 for material requirement only.



PUREPRO DOUBLE O'RING FILTER HOUSINGS

are manufactured of reinforced polypropylene, Clear, FDA approved Styrene-Acrylonitrile or Lexan material for 2.5" diameter cartridges. Most 9 7/8" and 10" length cartridges fit easily. Caps are available in 1/4" 3/8" and 1/2" Female NPT ports. Optional 3/8" quick connect ports are available. These housings can be used in applications such as pre and post filtration for Reverse Osmosis systems, undersink filtration, countertop systems, food service, ice machines and many more.

PUREPRO DOUBLE O'RING FILTER HOUSINGS

are Tested and Certified by International to ANSI Standard 42 for material and structural integrity requirements only.

MATERIALS OF CONSTRUCTION

• HOUSING	POLYPROPYLENE, SAN & LEXAN
• CAP	POLYPROPYLENE
• O-RING	BUNA-N
• MAXIMUM TEMPERATURE	125°F (51.7°C)
• MAXIMUM PRESSURE	100 PSI (7 BAR)

© PUREPRO USA CORP., ILLINOIS, U.S.A.